


## FEATURES

- » Rated voltage of 150V and capacitance of 6F
- » High performance module with low ESR
- » Designed with compact and light-weight package
- » Long lifetimes with up to 500,000 duty cycles\*
- » Passive cell balancing
- » Typical applications:
  - Wind turbine pitch control system
  - Industrial UPS and DVR



\* Image is not to scale.

ELECTRICAL SPECIFICATIONS		BMOD0006 P150 B02 EMHSR-0006C0-150R0C2
Rated Voltage, $V_R$		150 V <sub>DC</sub>
Surge Voltage <sup>1</sup>		171 V <sub>DC</sub>
Rated Capacitance, $C^2$		6 F
Capacitance Tolerance	Min. / Max.	0% / +20%
	Average <sup>4</sup>	+3% / +10%
Initial DC-ESR, $R_{DC}^3$	Max.	230 mΩ
	Average <sup>4</sup>	153 mΩ
Typical Leakage Current <sup>5</sup>	At 2.5V per cell	< 30 mA
Maximum Peak Current, Non-repetitive <sup>6</sup>		180 A
Maximum Stored Energy, $E_{max}^7$		18.7 Wh
Gravimetric Specific Energy <sup>7</sup>		3.1 Wh/kg
Usable Specific Power <sup>7</sup>		1.9 kW/kg
Impedance Match Specific Power <sup>7</sup>		4.0 kW/kg

TEMPERATURE SPECIFICATIONS	
Operating Temperature Range	-40 ~ 65°C
Storage Temperature Range (stored without charge)	-40 ~ 70°C

TYPICAL LIFETIME CHARACTERISTICS*	
DC Life at High Temperature <sup>8</sup> (at $V_R$ and 65°C)	1,500 hours
Projected DC Life at Room Temperature <sup>8</sup> (at $V_R$ and 25 ± 10°C)	10 years
Projected Cycle Life <sup>8</sup> (constant current charge-discharge from $V_R$ to 1/2 $V_R$ at 25 ± 10°C)	500,000 cycles
Shelf Life (stored without charge at 25 ± 10°C)	4 years

PHYSICAL SPECIFICATIONS	
Output Terminals	2×M5 screw holes (positive) / 2×M5 screw holes (negative) Use ring terminals that are 1.0mm or greater in thickness
Insulation Coordination	IEC 61287-1 (Category: OV II) Rated insulation voltage: 1kV DC or 2.8kV AC (at 50Hz, 10 sec) Rated impulse withstand voltage: 4kV DC
Protection Degree	IEC 60529 – IP 43
Vibration	IEC 60068-2-6 Table B-1
Shock	IEC 60068-2-27

\*Results may vary. Additional terms and conditions, including the limited warranty, apply at the time of purchase. See the warranty details for applicable operating and use requirements.

## UMU / MONITORING SPECIFICATIONS

Cell Balancing	Passive single cell balancing
Voltage Monitoring	Voltage Center Tap (Check in half voltage)
Temperature Monitoring	N/A
Power Terminal	2×M5 for each terminal


## TYPICAL THERMAL CHARACTERISTICS

Thermal Resistance, $R_{th}$	1.6 °C/W
Thermal Capacitance, $C_{th}$	4,700 J/°C
Usable Continuous Current ( $\Delta T = 15^{\circ}C$ ) <sup>9</sup>	6 A
Usable Continuous Current ( $\Delta T = 40^{\circ}C$ ) <sup>9</sup>	10 A

## SAFETY & ENVIRONMENTAL SPECIFICATIONS

RoHS	Compliant
REACH	Cell-level compliant
UL	Cell-level compliant

## DRAWING



## DIMENSION & WEIGHT

Length (±3.0)	Width (±3.0)	Height (±1.5)	Nominal Weight
378.0 mm	250.0 mm	83.0 mm	6.0 kg


## NOTE

### 1. Surge Voltage

- > Absolute maximum voltage, non-repetitive. The duration must not exceed 1 second.

### 2. Rated Capacitance (Measurement Method)

- > Constant current charge with 4CV [mA] to  $V_R$ .  
e.g. In case of 150V-6F module,  $4 \times 6 \times 150 = 3,600mA = 3.6A$
- > Constant voltage charge at  $V_R$  for 5 min.
- > Constant current discharge with 4CV [mA] to 24V.




$$C = \frac{I \times (t_2 - t_1)}{v_1 - v_2}$$

where  $C$  is the capacitance (F);  
 $I$  is the absolute value of the discharge current (A);  
 $v_1$  is the measurement starting voltage,  $0.8 \times V_R$  (V);  
 $v_2$  is the measurement end voltage,  $0.4 \times V_R$  (V);  
 $t_1$  is the time from discharge start to reach  $v_1$  (s);  
 $t_2$  is the time from discharge start to reach  $v_2$  (s)

### 3. Initial DC-ESR (Measurement Method)

- > Constant current charge with 4CV [mA] to  $V_R$ .
- > Constant voltage charge at  $V_R$  for 5 min.
- > Constant current discharge with 40CV [mA] to 140V.  
e.g. In case of 150V-6F module,  $40 \times 6 \times 150 = 36,000mA = 36A$



$$ESR_{DC} = \frac{\Delta v}{I}$$

where  $ESR_{DC}$  is the DC-ESR (Ω);  
 $\Delta v$  is the voltage drop during first 10ms of discharge (V);  
 $I$  is the absolute value of the discharge current (A)

### 4. Average

- > Typical value or percentage spread that may be present in one shipment

### 5. Typical Leakage Current (Measurement Method)

- > Typical leakage current of the module is the sum of the leakage current of the cell (measured at the rated voltage and at room temperature after 72 hours) and the bypass current created by the balancing circuit.

### 6. Maximum Peak Current

- > Current that can be used for 1-second discharging from the rated voltage to the half rated voltage under the constant current discharge mode

$$I = \frac{\frac{1}{2}V_R}{\Delta t / C + ESR_{DC}}$$

where  $I$  is the maximum peak current (A);  
 $V_R$  is the rated voltage (V);  
 $\Delta t$  is the discharge time (sec);  $\Delta t = 1$  sec in this case;  
 $C$  is the rated capacitance (F);  
 $ESR_{DC}$  is the maximum DC-ESR (Ω)

- > The stated maximum peak current should **not** be used in normal operation and is only provided as a reference value.

### 7. Energy & Power (Based on IEC 62391-2)

- > Maximum Stored Energy,  $E_{max}$  (Wh) =  $\frac{\frac{1}{2}CV_R^2}{3600}$
- > Gravimetric Specific Energy (Wh/kg) =  $\frac{E_{Max}}{Weight}$
- > Usable Specific Power (W/kg) =  $\frac{0.12V_R^2}{ESR_{DC} \times Weight}$
- > Impedance Match Specific Power (W/kg) =  $\frac{0.25V_R^2}{ESR_{DC} \times Weight}$

### 8. DC Life and Cycle Life Test

- > End-of-Life Conditions:
  - Capacitance: -20% from the minimum rated value
  - DC-ESR: +100% from the maximum specified initial value
- > Capacitance and ESR measurements are taken at  $25 \pm 10^\circ C$

### 9. Usable Continuous Current

- > Maximum current which can be used within the allowed temperature range under the constant current discharging mode

$$I = \sqrt{\frac{\Delta T}{R_{th} \times ESR_{DC}}}$$

where  $I$  is the maximum continuous current (A);  
 $\Delta T$  is the change in temperature ( $^\circ C$ );  
 $R_{th}$  is the thermal resistance ( $^\circ C/W$ );  
 $ESR_{DC}$  is the DC-ESR (Ω)

When ordering, please reference the Maxwell Model Number below.

<b>Maxwell Model Number:</b> BMOD0006 P150 B02	<b>Maxwell Part Number:</b> 133736	<b>Nesscap Model Number:</b> EMHSR-0006C0-150R0C2
---	---------------------------------------	--

**Maxwell Technologies, Inc.**  
Global Headquarters  
3888 Calle Fortunada  
San Diego, CA 92123  
USA  
Tel: +1 (858) 503-3300  
Fax: +1 (858) 503-3301

**Maxwell Technologies SA**  
Route de Montena 65  
CH-1728 Rossens  
Switzerland  
Tel: +41 (0)26 411 85 00  
Fax: +41 (0)26 411 85 05

**Maxwell Technologies, GmbH**  
Leopoldstrasse 244  
80807 Munich  
Germany  
Tel: +49 (0)89 4161403 0  
Fax: +49 (0)89 4161403 99

**Maxwell Technologies Shanghai Trading Co., Ltd**  
Room 1005, 1006, 1007  
No. 1898, Gonghexin Road,  
Jing An District, Shanghai  
200072  
P.R. China  
Tel: +86 21 3680 4600  
Fax: +86 21 3680 4699

**Nesscap Co., Ltd.**  
17, Dongtangiheung-ro 681beon-gil,  
Giheung-gu, Yongin-si,  
Gyeonggi-do  
17102  
Republic of Korea  
Tel: +82 31 289 0721  
Fax: +82 31 286 6767

The data in this document 3001972 corresponds to the data in Nesscap document 20170821 Rev3. The information in this document is correct at time of printing and is subject to change without notice. Images are not to scale.

MAXWELL TECHNOLOGIES, MAXWELL, MAXWELL CERTIFIED INTEGRATOR, ENABLING ENERGY'S FUTURE, NESSCAP, BOOSTCAP, D CELL, CONDIS and their respective designs and/or logos are either trademarks or registered trademarks of Maxwell Technologies, Inc., and/or its affiliates, and may not be copied, imitated or used, in whole or in part, without the prior written permission Maxwell Technologies, Inc. All contents copyright © 2017 Maxwell Technologies, Inc. All rights reserved. No portion of these materials may be reproduced in any form, or by any means, without prior written permission from Maxwell Technologies, Inc.